Enabling the TD Call feature on the Bridgemate

TD calls are initiated by players through the Bridgemate II device at the table. The 'Call TD' feature must be enabled through the Bridgemate settings in your scoring

program, or through the Bridgemate settings in BCS. To enable TD calls from BCS, follow these steps:

- 1. Start BCS and go to **Tools** \rightarrow **Options** \rightarrow **Bridgemate**.
- 2. Click on the second tab, Bridgemate II.
- 3. Enable the Allow TD calls from Bridgemate setting.

Options for tournament director		
PIN code: 0000		
□ 'No play' requires <u>I</u> D confirmation		
Allow TD calls from Bridgemate		

The Bridgemates' Call TD button is now enabled and can be used to call the Tournament Director.

Adding pagers and linking them to Sections

×			
Enable the Bridgemate paging system			
Add new pager			
Edit pager			
Delete pager			
Send test message			

To set up BCS to send messages to the pagers you need to tell BCS which sections should send to which addresses, there are a few steps to be taken:

Run BCS and go to **Tools** \rightarrow **Options** \rightarrow **General** \checkmark . Click the tab **Pagers**

2. Check "Enable the Bridgemate paging system"

- `3. Check "Add new pager"
- 4. Enter a pager ID i.e., the "**address**" to be used.
- 5. Click the sections that you want

For IDs (addresses) with fewer than 7 digits, the leading zeroes will be added automatically. The standard values are 5 zeroes followed by: 11, 22, 33, 44, 55, 66, 77 or 88.

The "Add new pager" button brings up this screen. Select the address to be used – in the "Pager ID" field. With "This pager is active" selected, specify:

- Use the pager for all sections
- Use the pager only for selected sections

A scoring computer may transmit TD Calls to multiple IDs (addresses); similarly, a director's pager may "listen" to more than one ID (address).

Notes:

- By default, the pager is set to 'active'. To add a pager ID but not make it active, make the settings as desired, then deselect **This pager is active**. (With this option deselected, the pager is still added to BCS, but the pager ID is not enabled and is not linked to any section.)
- Select the section for which this pager ID (address) should receive TD calls. All sections can be selected, or one-or-more individual Sections may be specified.
- Press **OK** to confirm the settings and add the pager to BCS.
- A pager ID (address) must be unique in BCS. If an ID already exists, it can't be added again.
- Sections can be assigned to multiple pager IDs (addresses). For example, when you configure pagers with the IDs 0000011 and 0000022, section A can be assigned to both pager IDs.

Disabling the paging system

To disable the paging system temporarily, simply go to **Tools** \rightarrow **Options** \rightarrow **General**, click on the **Pagers** tab, and untick the **Enable the Bridgemate paging system** checkbox. The paging system is now disabled. Note that the **Call TD** button is still active on the Bridgemate, unless you also disable the **Allow TD calls from Bridgemate** setting from the Bridgemate settings window.

Add new pager		×
Pager		
Pager ID:	0000011	Cancel
✓ This pager is	active	
 Use this provide the second sec	pager for all sections	
O Use this provide the second seco	pager only for selected sections:	
B C D E F G H H J K L M	N AAA NN AAA NNN O BB OO BBB OOO BBB OOO P CCC PP CCC PPP Q DD QQ DDD QQQ R EEE RR EEE RR S FF SS FFF SSS T GG TT GGG TTT U HH UU HHH UUU V III VW JJJ WWW X KK X KKK XXX Y LL YY LL YYY Z MM ZZ MMM ZZZ	